

**HIGH-FREQUENCY WELDING METHOD OF THERMOPLASTIC RESIN**

Patent Number: JP59184611  
Publication date: 1984-10-20  
Inventor(s): SUDA TSUTOMU  
Applicant(s):: SHOWA DENKO KK  
Requested Patent: ☐ JP59184611  
Application Number: JP19830058661 19830405  
Priority Number(s):  
IPC Classification: B29C27/04  
EC Classification:  
Equivalents:

---

**Abstract**

---

**PURPOSE:** To prevent a welded part from peeling off, by making use of a metal which is coated with adhesive substance as a heating source, in a high-frequency welding method of thermoplastic resin.

**CONSTITUTION:** A metal coated with adhesive resin and an adhesive agent is interposed between welded surfaces of high-frequency weldable thermoplastic resin, for example, high density polyethylene, low density polyethylene, polypropylene, polystyrene, polyvinyl chloride, polyamide, ethylene vinyl acetate copolymer, polyethylene terephthalate, ABS resin and AS resin, the above-mentioned welded surfaces made of the thermoplastic resin are touched each other by pressure to which high-frequency is applied, and welding is done by making the above-mentioned metal heat. The thermoplastic resin and adhesive substance and the adhesive substance and the metal are stucked firmly each other respectively after welding through the high-frequency like this, through which a peeling off phenomenon is solved.

---

Data supplied from the esp@cenet database - I2